

ARMORTEX®

BULLET/BLAST/FORCED-ENTRY PROTECTION PRODUCTS

O. F. 200 Opaque Fiberglass

UL 752 Level 2

NOMINAL THICKNESS: 3/8"

NOMINAL WEIGHT:

4.1 lbs per square foot

AVAILABLE SIZES:

3' X 8' 4' X 8'

3' X 9' 4' X 9'

3' X 10' 4' X 10'

MAKE UP

Multiple layers of woven roving ballistic grade fiberglass woven in house impregnated with a thermoset polyester resin and compressed into flat rigid sheets designed to capture projectile.

USES

Commercial, Residential, Government, Military, Banks, Credit Unions Retail, Check Cashing, Prisons, Courthouses, Police Stations, Safe Rooms, Schools, Public Safety Facilities Stadiums.

PERFORMANCE LEVEL

Underwriters Laboratory UL 752 11th Edition Standard for Bullet Resisting Equipment. One hour fire rated to ASTM E119-00a Building Construction and Materials.

AMMUNITION TESTED

.357 magnum jacketed lead soft point, 158 grain, 1,250 fps, 3 shots

INSTALLATION

Cut Armortex® Opaque Fiberglass using ordinary carpentry tools. We suggest using RemGrit® "Grit Edge" saw blade. Install using self tapping dry wall screws. Pre drilling may be required on 1 3/16" and thicker material. Drill using high speed steel twist drills bits. We recommend that you incorporate 4" overlap strips (battens) at seams.

WARRANTY

Materials and workmanship shall be warranted against defects for a period of two (2) years from the date of receipt at the project site.

Armortex ISO 9001